

Specifications (mm) - Nominal

Dimensions:

Length	13,730
Height	Top: 1,479
	Rear: 1,100
Skid Plate Height	1,280
King Pin Position	1,430
Wheel Base	9,500
Rear Overhang	2,700

Chassis Frame:

Main Rail Centres	1,040 mm
Skid Plate	10mm
Bumper Bar	Steel RHS with Side Infill Panels
Suspension Spread	2,700 mm
Coaming	125mm
Floor	Forklift Rated

Suspension:

Air-bag 190RH SAF Modul

Options available:

YORK/Hendrickson/BPW

Axle:

127 mm Round Axle, 10 Stud 285 PCD, Greased
Auto Slack Adjusters

Brake Kit:

WABCO EBS Brake Kit

Wheels & Tyres:

Steel Wheels 8.25 x 22.5 – 10 Stud 285 PCD / Size: 275/70 R22.5

Landing Gear: Compensating Foot (S-Foot)

Electrical:

12 Volt with 7 Pin socket at front
Multi-Volt LED Lighting

King Pin:

50mm Demountable JOST KZ1010 (190Kn)

Paint: 2 Pak: PPG

Signs: Long Vehicle | Do Not Overtake Turning Vehicle

Accessories & Options available:

- Front Side Gates (1,770mm x 1,525mm)
- Rear Side Gates (2,200mm x 1,915mm)
- Mudguards – Front & rear Steel Splash Guards in Main Beams
- Spare Wheel Carrier – Double wheel carrier incorporated in main beams (standard)
- Front and Rear load restraint racks (2415 x 1535mm)
- Steel Tool Box (1,200mm x 550mm x 400mm)
- 3- Way Flexi-use Twistlocks (1x40', 2x20', 1x heavy 20')
- Road train provision
- Gate Bow Carrier and Gate bow set
- 3-Way Flexi-use twistlocks (1x40', 2x20', 1x heavy 20')
- Galvanised Hydraulic Ramps – 800mm x 2,600mm | Ramp Angle: 21 degree | 10 tonne Ramp Rating
- Hydraulic Power Pack – 12 Volts DC, 200 BAR, 4lt Tank Min and Control Valve

Drawing - Nominal

