

# Specifications (mm) - Nominal

## Dimensions (mm):

|                    |                       |
|--------------------|-----------------------|
| Length             | 13,730                |
| Height             | 1,400                 |
| Skid plate height  | 1,280                 |
| King pin position  | 1,430                 |
| Wheelbase          | 9,500                 |
| Rear overhang      | 2,800                 |
| Tare weight (kg)   | 8,600 - standard spec |
| Suspension spread: | 2,800                 |

## Chassis Frame:

|                          |                                     |
|--------------------------|-------------------------------------|
| Mild grade steel SM490YA |                                     |
| Skid plate               | 10mm with 50mm demountable king pin |
| Bumper bar               | Steel RHS with side infill panels   |
| Coaming                  | 125mm                               |
| Floor                    | 3mm chequer plate                   |

## Suspension:

380RH, Air-Bag & Spring options

## Axle:

Round axle, 10stud 285PCD  
Greased with automatic slack adjusters

## Brake Kit:

WABCO 3 axle Tag trailer EBS kit  
Spring brakes on 3 axles

## Wheels & Tyres:

8.25x22.5- 10stud 285PCD/ Size11 R22.5

## Landing Gear:

2-speed 19" legs with Compensating S-Foot

## Electrical & Lighting:

Multi-Volt 12/24v  
LED Multi volt

## Paint:

2K finish – coaming, toolbox, hubs (1 colour)  
Underbody: Silver

## Signage:

Long Vehicle | Do not overtake turning vehicle

## Accessories & Options available:

### Included:

- Mudguards- Front & Rear steel splash guards in main beams
- Steel toolbox (1200x550x400mm)
- Front & Rear load restraint racks (2415x1535mm)
- Container beams and twist locks

### Available:

- Side gates (2200x1915mm)
- Road train provision
- Gate bow set with carrier (fitted to underbody)

# Drawing - Nominal

