



panus 
OCEANIA

CONVERTER DOLLY



A Panus Converter Dolly allows operators to hook-up to create road-train combinations and is best suited to A-Double Combination up to 85t GCM.

Design Features:

- ✓ Suited to A Double combination up 85t GCM
- ✓ WABCO EBS Braking
- ✓ LED Autolamps lighting and electrical system
- ✓ Fabricated using High Tensile Steel: Grade 700

www.panustrailers.com.au | 1300 467 268 | sales@panusocceania.com.au



DISCLAIMER: All measurements should be regarded as approximate only. Panus Oceania reserves the right to change these specifications without prior notice. All images are intended for illustration purposes only and do not necessarily represent the end product.

Specifications (mm) - Nominal

Dimensions (mm):

Length	4,562
Height	1,090
Draw bar length	1,850
Rear Overhang	1,237
Front overhang	1,475
Tare weight	2,450kg*

Chassis Frame:

Main Rail Centres	950mm
Bumper Bar	Steel RHS with Side Infill Panels

Suspension:

Air-bag 360RH SAF Modul

Options available:

YORK/Hendrickson/BPW

Axle:

127 mm Round Axle, 10 Stud 285 PCD, Greased, Auto Slack Adjusters

Brake Kit:

WABCO EBS Brake Kit

Wheels & Tyres:

Alloy Wheels 8.25 x 22.5 – 10 Stud 285 PCD / Size: 11 R22.5

Fifth Wheel:

SAF Holland

Electrical & Lighting:

12 Volt with 7 Pin socket at front

Multi-Volt LED Lighting

Paint:

2 Pak: PPG

Signs:

Long Vehicle

Accessories & Options available:

- Mudguards – Black
- Mudflaps with anti-sail bracket

Drawing - Nominal

