

Skeletal Trailer

Panus Skeletal Trailers are designed and refined from the customer-back, ensuring functionality and safety levels for the operators are paramount. With a focus on maximum operational flexibility, Panus Skels provide for 1x 40', 2x 20' or 1x 'Heavy 20' containers. Designed utilising wide beams and a low centre of gravity for added support and safety, all ancillary equipment is sourced and supported in Australia with the backing of a nationwide service and spares network. A Panus Skel lets you tackle your local wharf contract with 100% confidence!



Specification

Dimensions:	Length	12125 mm	Chassis Frame:	Main Rail Centres	1040 mm
	Width	2500 mm		Skid Plate	10 mm
	Skid Plate Height	1270 mm		Kingpin	50 mm demountable (190kN)
	King Pin Position	1100 mm		Bumper Bar	Steel RHS
	Wheel Base	8625 mm		Side Infill Panels at Rear	
Suspension:	SAF Holland Module – Air Bag (ADR Compliant)				
Axle:	Kedi Drum Brake Axle (ADR Compliant) 129mm Round, 10 Stud, 285 PCD, Greased, 6" Auto Slack Adjusters (ADR Compliant)				
Brake Kit:	EBS Brake Kit –	Wheels & Tyres:		Steel 10 Stud 285 PCD / 11R 22.5	
Landing Gear:	Standard 2 Speed with Rocker Foot	Twist Locks:		3-Way Twistlocks (1x20' / 2x20' / 1x40')	
Electrical:	Multi-Volt LED Lighting (ADR Compliant)	Paint:		Frame and Wheel Hubs 2 Pak	
Accessories:	Plastic Radius Guards with Mud Flaps at Rear Single Tyre Carrier Tool Box - STD 700 x 400 x 400	Options:		B-Double or Road Trailer Signage	

Drawing

