

Drop Deck Semi-Trailer



The Panus Drop Deck Semi Trailer allows you to maximise your cubic capacity, increasing your productivity and efficiency. Whether transporting high loads, large machinery or general freight pallets, the Panus Drop Deck model provides optimal space on both the lower and upper decks. The inclusion of full twist locks and hydraulic ramps at the rear, makes this trailer a truly versatile worker that will provide your haulage business with the competitive edge that is backed by a comprehensive dealer support network.



Specification

Dimensions:	Length	13,730 mm	Chassis Frame:	Main Rail Centres	1,040 mm
	Width	2,500 mm		Skid Plate	10 mm with 51 mm demountable King Pin (190kN)
	Height	Top	1,479mm	Bumper Bar	Steel RHS with Side Infill Panels
		Rear	1,100mm	Coaming	5 inch
	Skid Plate Height	1,280 mm	Floor	Forklift Rated/Flush	
King Pin Position	1,430 mm	Rear Overhang:	2,700 mm		
Wheel Base	9,500 mm	Tare Weight:	9,670 kg		
Suspension Spread:	2,700 mm				

Tailgate: Galvanised Hydraulic Ramps – 800mm x 2,600mm | Ramp Angle: 21 degree | 10 tonne Ramp Rating

Hydraulic Power Pack – 12 Volts DC, 200 BAR, 4lt Tank Min and Control Valve

Suspension: SAF Module U20/2500E29 190RH (ADR Compliant)

Axle: Kedi Drum Brake Axle (ADR Compliant)

127 mm Round Axle, 10 Stud 285 PCD, Greased, Auto Slack Adjusters

Brake Kit: Wabco EBS Tri Axle Brake Kit (ADR Compliant)

Wheels & Tyres: Steel Wheels 8.25 x 22.5 – 10 Stud 285 PCD / Superhawk HK867 - 275/70 R22.5

Landing Gear: Jost D200T – with compensating feet (S-Foot)

Twist Locks: 3-Way Twist Locks (1x 20' Container, 2x 20' Container, 1x 40' Container)

Electrical: Multi-Volt LED Lighting (ADR Compliant)

Hubodometer: Stemco DataTrac Pro Digital

Winch Track: Standard Winch Track Fitted to Right Hand Side of Trailer

Accessories: Front and Rear Splash Guards

Front and Rear Racks

Front Side Gates (1,770mm x 1,525mm)

Rear Side Gates (2,200mm x 1,915mm)

Paint:

Frame and Wheel Hubs 2 Pak

Spare Wheel Carrier – Double wheel carrier incorporated in main beams

Gate Carrier - NIL

Steel Tool Box (1,200mm x 550mm x 400mm)

Mudguards – Steel Splash Guards in Main Beams

Signs: Long Vehicle | Do Not Overtake

Drawing

