

# Skeletal Trailer Lead

Panus Skeletal Trailers are designed and refined from the customer-back, ensuring functionality and safety levels for the operators are paramount. With a focus on maximum operational flexibility, Panus Skels provide for 1x 40', 2x 20' or 1x 'Heavy 20' container when used in a B-Double configuration. Designed utilising wide beams and a low centre of gravity for added support and safety, all ancillary equipment is sourced and supported in Australia with the backing of a nationwide service and spares network. A Panus Skel lets you tackle your local wharf contract with 100% confidence!



## Specification

<b>Dimensions:</b>	Length	12115 mm	<b>Chassis Frame:</b>	High Tensile Grade 700 Steel	
	Width	2500 mm		Skid Plate	10 mm
	Skid Plate Height	1270 mm		Kingpin	50 mm demountable (190kN)
	King Pin Position	1105 mm		Container Beams:	5
	Wheel Base	8925 mm		Pedestals:	To suit 40ft Container
<b>Suspension:</b>	York Duratac Air Suspension (ADR Compliant)				
<b>Axle:</b>	York Roadbaron 10 x 285 Drum Brake Axle (ADR Compliant)				
<b>Brake Kit:</b>	Wabco EBS Tri-Axle Brake Kit	<b>Wheels &amp; Tyres:</b>	Alloy 10 Stud 285 PCD / 11R 22.5		
<b>5<sup>th</sup> Wheel:</b>	Jost JSK 36 Greasable 5 <sup>th</sup> Wheel	<b>Landing Gear:</b>	Standard 2 Speed with Rocker Foot		
<b>Twist Locks:</b>	3-Way Twistlocks (1x20' / 2x20' / 1x40')	<b>Electrical:</b>	Multi-Volt LED Lighting (ADR Compliant)		
<b>Paint:</b>	Frame and Wheel Hubs 2 Pak				
<b>Accessories:</b>	Plastic Radius Guards with Mud Flaps at Rear and Front				

## Drawing

